

Company Information

For more information about our products, parts or support:

- **CALL** (800) 633-5206
- **EMAIL** salesinfo@dii.doosan.com
- **VISIT** www.doosanportablepower.com

Parts Department

Toll Free: (800) 633-5206
Fax: (704) 883-3760

Service Department

Toll Free: (800) 633-5206
Fax: (704) 883-3760

Sales Department

Toll Free: (800) 633-5206
Fax: (704) 883-3770

National Rental Account Managers:

Pat Cangero
(315) 345-7372 cell
patrick.cangero@doosan.com

Marc James
(704) 576-1781 cell
(704) 883-3616 office
marc.james@doosan.com

District Manager Information & Territories

Territory	Name	Phone	Fax
East Central	Dan Lippert	(412) 298-5055	(412) 851-1346
West	Darrin Martin	(916) 761-6337	(916) 244-7223
Southeast	Dan Thomsen	(770) 330-5742	(866) 536-5169
South Central	Dave Matiko	(972) 679-2089	(866) 954-4610
Northeast	Joe Serigano	(631) 901-7004	(866) 536-5156
Mid-West	John Hargett	(480) 258-0129	(866) 924-3594
North Central	Rich Basarich	(847) 309-4332	(866) 884-2542
Mid-Atlantic	Zeke Hendrix	(704) 249-4117	(866) 270-5780

Canada

Eastern	Ron Vandergeld	(416) 200-1520	(877) 644-8226
Western	Trayson Mathias	(780) 975-1708	(866) 303-0685

Rental Equipment Portfolio



Experience Doosan Infracore Portable Power and our industry-leading support and service. Whatever the job, we have the solution. From our comprehensive range of Ingersoll Rand-branded air compressors, lighting systems and generators to our rugged and reliable light compaction equipment, we have a solution to fit your needs. Running a successful business takes more than powerful equipment. That is why we partner with an experienced global dealer network to stand beside you every step of the way. Doosan Infracore Portable Power — more than 100 years of providing excellence.





Air Compressors

Compressors	Free Air Delivery	Pressure
P65WK	65 cfm (1.8 m ³ /min)	100 psig (6.9 bar)
P90WIR	90 cfm (2.5 m ³ /min)	100 psig (6.9 bar)
P135WIR	135 cfm (3.8 m ³ /min)	100 psig (6.9 bar)
C185	185 cfm (5.2 m ³ /min)	100 psig (6.9 bar)
P185WIR	185 cfm (5.2 m ³ /min)	100 psig (6.9 bar)
P185WJD	185 cfm (5.2 m ³ /min)	100 psig (6.9 bar)
XP185WIR	185 cfm (5.2 m ³ /min)	125 psig (8.6 bar)
XP185WJD	185 cfm (5.2 m ³ /min)	125 psig (8.6 bar)
P250WIR	250 cfm (7.1 m ³ /min)	100 psig (6.9 bar)
P260WIR	260 cfm (7.4 m ³ /min)	100 psig (6.9 bar)
XP375WIR	375 cfm (10.6 m ³ /min)	125 psig (8.6 bar)
HP375WIR	375 cfm (10.6 m ³ /min)	150 psig (10.3 bar)
P425WIR	425 cfm (12 m ³ /min)	100 psig (6.9 bar)
VHP400WIR	400 cfm (11.3 m ³ /min)	200 psig (13.8 bar)
HP450WIR	450 cfm (12.7 m ³ /min)	150 psig (10.3 bar)
P600WIR	600 cfm (17 m ³ /min)	100 psig (6.9 bar)

Common Applications

- road construction
- pavement breaking
- sandblasting
- sprinkler blow out
- painting
- pneumatic tools
- pressure testing

Mobile Generators

Generators	Prime Output	Run Time (100% Load)
G10	10 kVA (10 kW)	26.4 hrs
G25	25 kVA (20 kW)	20.7 hrs
G40	35 kVA (28 kW)	20.5 hrs
G70	72 kVA (58 kW)	24.9 hrs
G90	94 kVA (75 kW)	24.6 hrs
G145	144 kVA (115 kW)	21.8 hrs
G185	183 kVA (146 kW)	23.2 hrs
G240	239 kVA (191 kW)	18.8 hrs
G290	290 kVA (232 kW)	20.9 hrs
G450	456 kVA (365 kW)	22.3 hrs
G570	570 kVA (456 kW)	18.4 hrs

Common Applications

- jobsite power
- back up power
- special events
- sporting events
- electric tools

Product improvement is a continuing goal at Doosan Infracore Portable Power. Designs and specifications are subject to change without notice or obligation. Nothing contained in this brochure is intended to extend any warranty or representation, expressed or implied, regarding the products described herein. Any such warranties or other terms and conditions of sale shall be in accordance with standard Doosan Infracore Portable Power terms and conditions of sale for such products, which are available upon request.

Lighting Systems

Model	kW	Runtime
LightSource	6 kW	52 hrs
L6	6 kW	52 hrs
L8	8 kW	48 hrs
L20	20 kW	13 hrs (100% load) 69 hrs (4 lights only)

Model	Lamps	Lighted Area
BL2000	(2) 1000 watt bulbs	15000 sq ft

Common Applications

- road construction
- security
- jobsite lighting/power
- special events
- emergency response
- general construction
- parking areas
- disaster relief
- airports

Light Compaction

Upright Rammers*	Operating Weight	Foot Size (W x L)
RX-264H	127 lb (58 kg)	9 in x 13 in (230 mm x 330 mm)
RX-304H	156 lb (71 kg)	11 in x 13 in (270 mm x 330 mm)
RX-344H	157 lb (72 kg)	11 in x 13 in (270 mm x 330 mm)

* Standard Honda engine. Narrow foot aftermarket options available

Single-Direction Vibratory Plate Compactors	Operating Weight	Plate Size (W x L)
BX-6WH*	150 lb (70 kg)	16 in x 21 in (400 mm x 525 mm)
BX-8WH*	195 lb (90 kg)	19 in x 23 in (480 mm x 585 mm)
BX-12WH*	245 lb (110 kg)	22 in x 26 in (550 mm x 650 mm)
BX-60WH**	182 lb (83 kg)	17 in x 22 in (430 mm x 565 mm)
BX-80WH**	182 lb (83 kg)	20 in x 22 in (500 mm x 565 mm)
BX-120WH**	244 lb (111 kg)	22 in x 23 in (550 mm x 575 mm)
VP-8RH***	293 lb (133 kg)	20 in x 19 in (500 mm x 480 mm)

* Standard fixed water tank and Honda engine
 ** Standard removable water tank and Honda engine. Wheel/carry cart accessory available
 *** Four removable rollers for use on bricks and sub-base materials. Roller size (DXL) is 3.4 in x 19 in (86 mm x 480 mm)

Reversible Vibratory Plate Compactors	Operating Weight	Plate Size (W x L)
BXR-60H*	158 lb (72 kg)	14 in x 19 in (350 mm x 470 mm)
BXR-100H	330 lb (150 kg)	15 in x 25 in (390 mm x 630 mm)
BXR-200H	518 lb (235 kg)	18 in x 29 in (450 mm x 740 mm)
BXR-300E**	716 lb (325 kg)	18 in x 34 in (450 mm x 860 mm)

* Wheel/carry cart accessory available
 ** Plate extensions accessory available
 (H: Honda gasoline engine, E: Yanmar diesel engine)

Single Drum Walk-Behind Rollers	Operating Weight	Drum Width
SX-170H	595 lb (270 kg)	22.0 in (560 mm)

Double Drum Walk-Behind Rollers	Operating Weight	Drum Width
DX-500E	1300 lb (590 kg)	22.6 in (575 mm)
DX-600E	1410 lb (640 kg)	25.0 in (635 mm)
DX-600H	1345 lb (610 kg)	25.0 in (635 mm)
DX-700E	1630 lb (740 kg)	25.5 in (650 mm)
DX-700H	1565 lb (710 kg)	25.5 in (650 mm)

* Standard electric start
 (H: Honda gasoline engine, E: Kubota diesel engine)

Common Applications

- landscaping/paving stones
- sub-base compaction
- retaining walls
- backfill compaction
- asphalt compaction
- drainage ditches