

BL2000 Balloon Light



Ingersoll-Rand Balloon Light Self-inflating Illumination Unit

Efficient — Diffuses strong, glare-free light over a 360-degree area.

Versatile — Mounts onto optional stands or can be fixed directly onto any piece of equipment.

Quick, easy setup — Unit inflates in less than one minute and provides instant illumination once fully inflated.

Lightweight — Packs into a container small enough to keep in a car. Weighs less than 40 lbs.



BL2000 Balloon Light

Specifications

OPTIONAL MOUNTING DEVICES*



- **Pole Mount (CPN 22367981)** — 7- to 15-ft extension mounts to any equipment using locally sourced hardware — U-brackets, welding, etc.




- **Hitch Mount (CPN 22367973)** — 7- to 15-ft extension mounts directly to a vehicle's hitch receiver.

- **Tripod Stands** — 7- to 24-ft extension for stand-alone uses (as seen on cover).

* All mounting devices sold separately.

APPLICATIONS

- Construction
- Disaster Relief
- Drilling
- Farming / Agriculture
- Guard Rail Installation
- Landscaping
- Mining
- Paving
- Railroad Repair / Maintenance
- Road Repair / Maintenance

MODEL	BL2000
SPECIFICATIONS	
Diameter in (m)	43.3 (1.1)
Standard Plug Type	 3-prong
Power Supply amps (volts)	15 – 20 (110 – 130)
Lamps W	2 x 1000
Lighted Area sq ft (m ²)	15,000 (1400)
Operating Height ft (m)	7.5 – 15 (2.5 – 5)
Total Weight lb (kg)	36 (16)
Inflation Time sec	45
Wind Speed Resistance mph (km/h)	63 (100)

Product improvement is a continuing goal at Ingersoll-Rand. Designs and specifications are subject to change without notice or obligation.

