

PRO-TEC

IR Compressor Fluids offer quality protection to maximize the performance of your equipment.

Advantages:

- Designed especially for Ingersoll Rand compressor units
- New compressors units are factory filled with PRO-TEC to provide immediate protection
- Extends equipment service life
- Superior lubricating film strength
- Compatible with all seal materials
- Superior equipment wear protection
- Excellent low temperature performance
- Reduced foaming & fluid loss in severe service conditions
- Excellent lubrication under normal and severe operating conditions



| <i>Properties</i> | <i>Measurement</i> |
|--------------------------|----------------------------|
| Gravity, API | 32.2 |
| Specific Gravity | .869 |
| Flash Point COC, C(F) | 188° (370°) |
| Pour Point C(F) | -43° (-45°) |
| Ambient Temperature C(F) | -23° to 52° (-10° to 125°) |

| <i>Viscosity</i> | |
|------------------|-----|
| @40C (cSt) | 36 |
| @100C (cSt) | 7.5 |
| Viscosity Index | 163 |

| <i>Packaging</i> | |
|----------------------|----------|
| 1 Gallon | 36899698 |
| 5 Gallons | 36899706 |
| 55 Gallons | 36899714 |
| 1 Tote – 375 Gallons | 36899722 |

For more details, please contact Ingersoll-Rand
Utility Equipment Customer Support
800.633.5206