



# Doosan Portable Power C185 Gas Spec Sheet



Model	C185WKUBG
<b>COMPRESSOR ROTARY SCREW/SINGLE-STAGE</b>	
Free-Air Delivery – cfm (m3/min)	185 (5.2)
Rated Operating Pressure – psig (bar)	100(6.9)
Pressure Range – psig (bar)	80 – 125 (5.5 – 8.6)
Air Discharge Outlet Size – in (mm)	0.75 (19)
Air Discharge Outlet Quantity	2
Fuel Tank Capacity – gal (L)	24 (89)
<b>ENGINE</b>	
Make/Model	Kubota WG2503-G-E3
Emissions Tier Level	Meets EPA Reg
Number of Cylinders	4
Displacement – cu in (L)	153 (2.5)
Rated Speed – rpm	2600
Idle Speed – rpm	1700
Bhp @ Rated Speed (kW)	49.9 (37.2)
Electrical - volts	12
Hours of Operation @ Full Load	6
<b>DIMENSIONS WITH RUNNING GEAR</b>	
Length – in (mm)	133.7 (3396)
Width – in (mm)	61.7 (1567)
Height – in (mm)	63 (1600)
Track Width – in (mm)	54 (1372)
Tire Size – in	13
Shipping Weight – w/o fuel – lb (kg)	1905 (864)
Working Weight – w fuel – lb (kg)	2037 (924)
<b>DIMENSIONS WITHOUT RUNNING GEAR</b>	
Length – in (mm)	77.6 (1971)
Width – in (mm)	51.3 (1303)
Height – in (mm)	52.7 (1339)
Shipping Weight – w/o fuel – lb (kg)	1706 (774)
Working Weight – w fuel – lb (kg)	1837 (833)

## Key Features

- Low acquisition cost with the reliable and efficient Kubota gasoline engine means better ROI.
- Gas alternative provides lower noise and less weight than diesel.
- Single-piece canopy design, made of composite material, is lightweight, aerodynamic and virtually indestructible.
- Simple and intuitive control interface for easy operation.

