



Doosan Portable Power XP1000 HP915 Spec Sheet



Model	XP1000	HP915
COMPRESSOR ROTARY SCREW/SINGLE-STAGE		
Free-Air Delivery – cfm (m3/min)	1000 (28.3)	915 (25.9)
Rated Operating Pressure – psig (bar)	125 (8.6)	150 (10.3)
Pressure Range – psig (bar)	80 - 150 (5.5 - 10.3)	80 - 175 (5.5 - 12.1)
Air Discharge Outlet Size – in (mm)	2-inch NPT (50.8)	
Air Discharge Outlet Quantity	1	
Fuel Tank Capacity – gal (L)	128 (485)	
ENGINE		
Make/Model	Cummins/QSL9	
Emissions Tier Level	Tier 4 Final (T4F)	
Number of Cylinders	6	
Displacement – cu in (L)	543 (8.9)	
Rated Speed – rpm	1800	
Idle Speed – rpm	1200	
Bhp @ Rated Speed (kW)	303 (226)	
Electrical - volts	24	
Hours of Operation @ Full Load	8.7	
DIMENSIONS WITH RUNNING GEAR		
Length – in (mm)	226.6 (5748)	
Width – in (mm)	82.6 (2098)	
Height – in (mm)	101.3 (2573)	
Track Width – in (mm)	69.3 (1760)	
Tire Size – in	16	
Shipping Weight – w/o fuel – lb (kg)	10461 (4745)	
Working Weight – w fuel – lb (kg)	11309 (5130)	
DIMENSIONS WITHOUT RUNNING GEAR		
Length – in (mm)	171 (4343)	
Width – in (mm)	83 (2108)	
Height – in (mm)	95 (2413)	
Shipping Weight – w/o fuel – lb (kg)	9740 (4418)	
Working Weight – w fuel – lb (kg)	10765 (4883)	

Key Features

- Enclosure design includes gull wing doors, drop down tailgate doors and a cooler access hatch to provide the best servicing capabilities in the industry.
- The efficient central drain system allows operators to easily drain fluids from the radiator and oil and fuel tanks to a central location, without having to crawl under the machine.
- Operation is made easy and efficient with a control panel that offers more detail and preloaded resources than any other control panel in the market.
- Equipped with a Doosan-designed and manufactured airend that offers a highly efficient rotor profile, requiring less horsepower to deliver high-volume cfm output.
- Built to excel in rugged conditions with a heavy-gauge steel enclosure, heavy-duty tandem-axle running gear and construction-grade pedestal jack stand.
- Available with IQ System® that provides Instrument Quality air.

